



### SWSS1631B Chipping Spreader

SWSS1631B chip spreader is truck-mounted design, and mainly used for, simultaneously spraying asphalt and spreading chips(crushed stone), which ensure the best binding between asphalt and chips. It is cost-effective, making the road surface highly wearproof, highly antiskid and waterproof, extending, the service life of the road, quickly resuming the traffic etc. It is proved to be advanced, scientific and highly efficient.

Main Technical Specification	
Max. spreading width	3100mm
Aggregating specification	S3—S24mm
Spreading capacity	0.5—50m <sup>3</sup> /k m <sup>2</sup>
Working speed	10—20k m <sup>2</sup> /h
Total width	2400mm
Hanging part	1500mm
Total weight	1.3t
Overall dimensions	2400×1810×1620 (L×W×H)
Chassis Technical Requirements	
Batteries	DC12×2
Hydraulic tank capacity	≥60L
Dump body width(inside)	2300±10mm
Dump body side rake	≤2°
Dump body back boundary line straightness	≤2mm
Dump body back column verticality	≤2mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572