

Medium Wheel Loader LGL50D

WD615G220
Direct injection,water cooled
162KW
2200rpm
200g/Kw.h
5000Kg
16500Kg
3m3
145kN
3050mm
1290mm
45°
^m 210mm
6300mm
5795mm
±11°
≤6.8s
≤3.8s
≤1.2s

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China Post Code: 201100 E-mail: info@shlongji.com

Tel: +86-21-541-71571 Fax: +86-21-541-71572

Model of oil pump	CBGj3100
System pressure	16Мра
Model of multi-way directional valve	Double valve, mechanical operation
Axle And Tyre	
Type of main reducer	Spiral bevel gear, single stage
Gear ratio of main reducer	5.286
Type of final reducer	Single stage planetary
Gear ratio of final reducer	4.4
total ratio	23.258
Max. tractive force	123kN
Tyre size	20.5-25
Transmission System	
Torque Converter	
Туре	Single stage, double turbine, colligation(Sinoway)
Torque ratio	4
Cooling type	Pressure oil circulating
Gear box	•
Туре	Power shift(Sinoway)
Gear shifts (Forward/Reverse)	F2/R1
Traveling speed(Km/h)	•
Forward/Reverse I	11.5/16
Forward II	38
Braking System	•
Service brake	Double pipes, gas drive oil, four wheel disc type braking
Air pressure	0.68Mpa
Parking brake	Hand braking
Steering System	•
Туре	Hinge joint frame, priority type, flux expanding turning system
Model of steering pump	CBGJ2080
System pressure	14MPa
Articulated steering angle	38±1°(L/R)
Dimensions	•
Length(with bucket on ground)	7500mm
Width(to outside of wheels)	2990mm
Height(To the top of the cab)	3400mm
Bucket width	2975mm
Wheel base	2760mm
Tread	2240mm
Ground clearance	480mm
Service Capacities	
Fuel tank	220L
Engine crank case	22L
Converter and gear box	45L
<u>. </u>	•

Shanghai Longji Construction Machinery Co., Ltd.
Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100 E-mail: info@shlongji.com Tel: +86-21-541-71571 Fax: +86-21-541-71572

Hydraulic tank	210L	
,	F · · -	