

QLB40 mobile asphalt batching plant

QLB40 mobile asphalt batching plant comes with product temperature of 120°C - 165°C , feeder hopper capacity of 1.2m3, aggregate size of less than 50mm, aggregate bin of $3\times5\text{m}3$, which adopts towing chassis for easy transport and installation.

Main Technical Specification	
Capacity	40ton/h
Feeder hopper capacity	1.2m3
Concrete output	1.2m3
Aggregate size	≤50mm
Aggregate Bins	3×5m3 each, accumulative scale
Accuracy	
Aggregate	≤2000kg±3%
Fly ash	≤180kg±2%
Bitumen	≤180kg±2%
Product temperature	120~165 Celsius degree,adjustable
Total consumption	125 kW (Oil burner)
Mill Power	30kW (Coal burner)
Coal requirement	
Volatile Percentage	≥25%
Low heat value	≥6500kcal/kg
Melting point	1500°C
Moisture	≤3%
Powder percentage	≤12%
Diameter	≥100mesh
Configuration Table	
Aggregate Dosage	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100 E-mail: <u>info@shlongji.com</u> Tel: +86-21-541-71571 Fax: +86-21-541-71572

Aggregate hopper	3units	
Opeing device	6units	
Weighing hopper	1unit	
Sensor	3units	
Solenoid valve	3units	
Cylinder	3units	
Framework	1set	
Electric roller	1unit	
Collecting belt	1set	
Tension device	1set	
Roller	1set	
Cleaner	1set	
Burner		
Burner	1unit	
Blower	1unit	
Blower motor	1unit	
Main oil pump	1set	
Triangle belt	1unit	
High pressure oil pump	1set	
Fire-resistant brick	1set	
Electronic ignition system	1unit	
Dryer		
Drying drum(?2100mm)	1unit	
Big gear loop	1unit	
Decelerate case	1unit	
Motor	1unit	
Triangle belt	2units	
Seal loop	2units	
Frequency inverter	1unit	
Aggregate Elevator System		
Trail and skip	1set	
Feeder bucket device	1unit	
Reducer	1unit	
Limit switch	3units	
Filler Scale		
Weighing hopper	1unit	
Screw conveyor	1unit	
Reducer	1unit	
Sensor	1unit	

Tel: +86-21-541-71571 Fax: +86-21-541-71572