



### LGS0712GLQ Standard Asphalt Distributor

LGS0712GLQ asphalt distributor is an economical type with compact structure and high working efficiency, which is mainly composed of truck chassis, asphalt tank, asphalt pumping and spraying system, heating system, hydraulic circuit, pneumatic circuit and operation panel. It can spray rubber asphalt, hot asphalt, emulsified asphalt, modified asphalt, etc.

Engine	
Model	WD415.18
Type	Water-cooled, turbocharged
Rated power	137KW
Rated speed	2200rpm
Main Technical Specification	
Chassis model	ZZ1121G4715W
Spray width	200-4500mm
Spray volume	0.5-2.0kg/m <sup>2</sup>
Asphalt tank volume	6700L
Asphalt heater	Imported diesel oil burner
Spray media	Hot(modified)asphalt, diluted asphalt, emulsified asphalt, etc
Spray precision	±2°
N.V.W	7500kg
Payloading capacity	7000kg
G.V.W	14500kg
Axle loading capacity(F/R)	7000/7500kg
Max. traveling speed	90km/h
Approach angle	24.5°
Departure angle	18°
Transmission System	
Mechanical type	
Ratio	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Forward	9.01,5.24,3.22,2.20,1.50,1.00
Reverse	8.30
Axle And Type	
Front axle	STEYR
Rear axle	STEYR
Ratio	4.87
Tyre size	9.00-20
Steering System	
Hydraulic steering	
Clutch And Brake	
Single-plate dry coil-spring clutch diameter 420	
Service brake	Air brake
Parking brake	Mechanical
Dimensions	
Overall length	8530mm
Overall width	2496mm
Overall height	3350mm
Wheel base	4700mm
Tread(F/R)	1940/1800mm

**Shanghai Longji Construction Machinery Co., Ltd.**

**Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China**

**Post Code: 201100**

**E-mail: [info@shlongji.com](mailto:info@shlongji.com)**

**Tel: +86-21-541-71571**

**Fax: +86-21-541-71572**