

## LGS0816GLQ Standard Asphalt Distributor

LGS0816GLQ asphalt distributor is an improved type on the basis of LGS0812GLQ with 6000mm max. distributing width, which is mainly composed of truck chassis, asphalt tank, asphalt pumping and spraying system, heating system, hydraulic circuit, pneumatic circuit and operation panel. It can spray rubber asphalt, hot asphalt, emulsified asphalt, modified asphalt, etc.

Each nozzle separately controlled for regulating spray width randomly

PLC regulating spray volume automatically

Imported heat-resistance seal elements

Burner hood of optimization design preventing damages by asphalt eruption through manhole

High-viscosity asphalt pump

Warning signs and lighting installation for working at night

Gravity emptying device

Grandy emptying device	
Engine	
Model	WD15.92/93
Туре	Water-cooled, turbocharged, Tier Ⅲ
Rated power	196/213KW
Rated speed	2200rpm
Main Technical Specification	
Chassis model	ZZ1161M5011C
Spray width	200-6000mm
Spray volume	0.2-3.0kg/m²
Asphalt tank volume	8000L
Asphalt heater	Imported diesel oil burner
Spray media	Hot(modified)asphalt, diluted asphalt, emulsified asphalt, etc
Spray precision	±2°
N.V.W	8000kg
Payloading capacity	7870kg
G.V.W	16000kg
Axle loading capacity(F/R)	8000/8000kg
Max. traveling speed	85/90km/h
Approach angle	20.5°

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100 E-mail: <u>info@shlongji.com</u> Tel: +86-21-541-71571 Fax: +86-21-541-71572

Departure angle	17°	
Transmission System		
F8/ZF6 mechanical type		
Ratio(F8)		
Forward	11.4,7.94,5.63,4.06,2.81,1.96,1.00	
Reverse	11.35	
Ratio(ZF6)		
Forward	9.01,5.24,3.22,2.20,1.50,1.00	
Reverse	8.30	
Axle And Type		
Front axle	JW07	
Rear axle	M1249/STR	
Ratio	4.87/4.8	
Tyre size	12.00-20	
Steering System		
JL80Z/ZF,hydraulic steering		
Clutch And Brake		
Single-plate dry coil-spring clutch, diameter 420		
Service brake	Dual circuit compressed air brake	
Parking brake	Spring energy operating on rear wheels	
Dimensions		
Overall length	9000mm	
Overall width	2496mm	
Overall height	3420mm	
Wheel base	5000mm	
Tread(F/R)	2047/1995mm	

Tel: +86-21-541-71571 Fax: +86-21-541-71572