



LG5350THB-42 Truck Mounted Concrete Pump

Pumping system	
Transport capacity in theory	125m ³ /h
Pumping capacity index	586MPa×m ³ /h
Max. concrete pressure	8.5MPa
Bucket volume	620L
Bucket top surface height from the aggregate place	1400mm
Distribution valve form	S shape valve
Booms	
Max. aggregate carrying radius	38m
Max. aggregate carrying height	41.8m
Max. aggregate carrying depth	28m
Open height of aggregate carrying pipe	10000mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572

Distance between front landing legs	8500mm
Distance between rear landing legs	8500mm
Distance between front and rear landing legs	8490mm
Delivery pipe's diameter	125mm
Tail hose's length	3m
Aggregate carrying pipe's rotary range	365°
Boom's section number	4
Rotary angle of each boom section	92°/180°/80°/260°
Remote-control distance	33m
Chassis and whole vehicle	
Max. speed	85km/h
Min. turning radius	10200mm
Brake distance	10m
Approach angle	24°
Departure angle	15°
Chassis model	CXH50T/ISUZU/HOWO
Wheel base between the first and the second axle	1850mm
Wheel base between the second and the third axle	4605mm
Wheel base between the third and the fourth axle	1310mm
Front tread	2065mm
Rear tread	1855mm
Engine max.output power	286kw(1800r/min)
Engine max.output torque	1422N·m(1100r/min)
Max. climbing grade	35%
Fuel consumption limit	40L/100km
Outer size(length×width×height)	13650×2490×3960mm
Full-load general weight	35000kg

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572