



Walk-Behind Vibratory Roller LGW025

Fully closed hydraulic driving mechanism

Japanese Robin EY20D gasoline engine

Adjustable operating handle, which is easy and simple for the operators

Operating handle integrating the functions of reversing, the throttle and the starting of oscillation

Engine	
Model	CF186F
Type	Vertical, air-cooled, direct injection
Rated power	5.68Kw
Rated speed	2600rpm
Main Technical Specification	
Operating weight	780kg
Front static linear load	46N/cm
Rear static linear load	73N/cm
Vibrating frequency	48Hz
Vibrating amplitude	0.25mm
Centrifugal force	12Kn
Vibrating drum width	600mm
Vibrating drum diameter	405mm
Vibrating drum rim thickness	12mm
Traveling speed	2.5km/h
Grade-ability	40%
Turning radius	2700mm
Steering angle	30°
Dimensions	
Overall length	2330mm
Overall width	795mm
Overall height	1050mm
Wheel base	6000mm
Service Capacities	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Fuel tank	5L
Water tank	30L

Shanghai Longji Construction Machinery Co., Ltd.
Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100 **E-mail: info@shlongji.com**
Tel: +86-21-541-71571 **Fax: +86-21-541-71572**