



### LGW08DB Walk-Behind Vibratory Roller

LGW08DB manual vibrating road roller can be used for municipal road construction, highway maintenance, and rolling work at narrow road surface, such as foundation of groove wider than 0.8m, building construction, backfilling for pipeline and gymnasium ground.

Nice shape and compact structure.

All wheel drive, strong climbing capability.

With both electrical and manual startup devices.

Designed with guide wheel and joystick.

Engine	
Model	CF186F
Type	Vertical, air-cooled, direct injection
Rated power	5.68Kw
Rated speed	2600rpm
Main Technical Specification	
Operating weight	780kg
Front static linear load	46N/cm
Rear static linear load	73N/cm
Vibrating frequency	48Hz
Vibrating amplitude	0.25mm
Centrifugal force	12Kn
Vibrating drum width	600mm
Vibrating drum diameter	405mm
Vibrating drum rim thickness	12mm
Traveling speed	2.5km/h
Grade-ability	40%
Turning radius	2700mm
Steering angle	30°
Dimensions	
Overall length	2330mm
Overall width	795mm
Overall height	1050mm
Wheel base	6000mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Service Capacities	
Fuel tank	5L
Water tank	30L

**Shanghai Longji Construction Machinery Co., Ltd.**  
**Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China**  
**Post Code: 201100**                      **E-mail: [info@shlongji.com](mailto:info@shlongji.com)**  
**Tel: +86-21-541-71571**                      **Fax: +86-21-541-71572**