



Wheel Excavator LGEL80

Engine	
Model	Cummins B3.3(UK)
Type	Direct injection,water cooled
Rated power	60kw
Rated speed	2200rpm
Main Technical Specification	
Operating weight	8200kg
Standard bucket capacity	0.35m ³
Slewing speed	12rpm
Stick digging force	39.3KN
Bucket digging force	58KN
Hydraulic System	
Main pump	KAWASAKI
Main valve	KAWASAKI/Parker
Motor	TOSHIBA/Parker
Hydraulic flow rate	170L/min
Hydraulic pressure	30Mpa
Traveling System	
Front and rear axle driving , with wheel hub and front axle steering	
Traveling speed	25Km/h
Grade ability	40%
Dimensions	
Overall length	6250mm
Overall width	2160mm
Overall height of boom	2600mm
Overall height of cab	2750mm
Engine cover height	1970mm
Counterweight clearance	1045mm
Ground clearance	260mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Upperstructure width	2160mm
Rear-end length/Slewing radius	2850mm
Wheel base	2400mm
Overall width of blade	2120mm
Overall height of blade	450mm
Front overhang	930mm
Overall width with outrigger extended	2850mm
Rear overhang	780mm
Operating Scope	
Stick length	1780mm
A:Max cutting height	7250mm
B:Max dumping height	5350mm
C:Max digging depth	3930mm
D:Max reach	6460mm



Wheel Excavator LGEL80

Engine	
Model	Cummins B3.3(UK)
Type	Direct injection,water cooled
Rated power	60kw
Rated speed	2200rpm
Main Technical Specification	
Operating weight	8200kg
Standard bucket capacity	0.35m ³
Slewing speed	12rpm
Stick digging force	39.3KN
Bucket digging force	58KN
Hydraulic System	
Main pump	KAWASAKI

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Main valve	KAWASAKI/Parker
Motor	TOSHIBA/Parker
Hydraulic flow rate	170L/min
Hydraulic pressure	30Mpa
Traveling System	
Front and rear axle driving , with wheel hub and front axle steering	
Traveling speed	25Km/h
Grade ability	40%
Dimensions	
Overall length	6250mm
Overall width	2160mm
Overall height of boom	2600mm
Overall height of cab	2750mm
Engine cover height	1970mm
Counterweight clearance	1045mm
Ground clearance	260mm
Upperstructure width	2160mm
Rear-end length/Slewing radius	2850mm
Wheel base	2400mm
Overall width of blade	2120mm
Overall height of blade	450mm
Front overhang	930mm
Overall width with outrigger extended	2850mm
Rear overhang	780mm
Operating Scope	
Stick length	1780mm
A:Max cutting height	7250mm
B:Max dumping height	5350mm
C:Max digging depth	3930mm
D:Max reach	6460mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572